

Power generation

Durable design for hostile environment

When an Arizona power plant wanted to increase the capacity of pumps used to avoid the possibility of overflow. It was imperative the pumps be protected from the elements, making conventional solutions untenable. However, fluid handling consultancy, Quadna Inc, came up with the answer.

The Springerville Generating Station is a state-of-the-art coal-fired power plant in Springerville, Arizona. It has three units and a third has recently been added. Unit 4 is a 400 MW coal-fired generating unit and its owners, Salt River Project (SRP) and one of Arizona's largest utility companies, wanted to increase the capacity of pumps used to move effluent from one pond to another to avoid the possibility of overflow.

Effluent water from the Unit's cooling towers is collected in a lined pond and the plant's pumping system delivers water to one of two evaporation ponds. To help them find a solution, the company approached Phoenix, Arizona-based Quadna Inc, a consultancy and equipment supplier which engineers, fabricates and services mechanical systems that move fluids and gases for industrial applications.

The customer asked to Lisa Poole, Quadna's manager of engineering and sales, to



Springerville Generating Plant in northern Arizona

investigate the concept of using a vertical turbine on a floating barge on the pond. As Poole related: "Originally, we received a specification request to supply one stainless steel pump barge capable of supporting two submersible pumps (including motors) with an associated piping manifold that would extend to the edge of the barge," says Poole. "The plan for the ancillary barge equipment includes a discharge manifold with flanged connections, check valves, isolation valves and an overhead trolley for servicing the two pumping units. The floating barge also would house a 40-foot-long floating walkway that would be used to access the shoreline and a duplex pump control panel."

Although Quadna has supplied the type of equipment specified many times in the past, the price for the barge pumping system for this particular application proved more than the client was willing to spend. This option also posed an additional problem: the customer did not want any impingement of the liner so the pumps and pipe could not be secured.

There were other challenges too. The generating station is located in an area known as the Gateway to the White Mountains. The project site is remote and, at an elevation of 7,000 ft, the solution had to accommodate occasional sub-zero temperatures and fluctuating pond levels the result of rainwater and snow run-off.

Poole says the Quadna team discussed other viable options with the client. The chosen option would use submersible turbines

supported by a pipe at the edge of the pond on a 45° angle or self-priming pumps that would be situated on the dry bank of the pond.

Poole went on to explain: "In the White Mountains of Arizona, temperatures can range from 12° to 94° with wind speeds that whip up to 90 mph. So, it was imperative the pumps be protected from the elements."

Understanding the strict parameters of the project, Quadna pooled extensive engineering resources from its Phoenix and



The pump house enclosure unit. Photo courtesy Quadna.

Golden offices to tackle the customer's needs. The team decided to utilize two Gorman Rupp T2 series model T2A60 v-belt driven pumps with 10 hp US Electric Motors. These pumps were chosen for their reliability and because of the limited net positive suction head (NPSH) available.

Next, the pump system experts tackled the pump protection issue. Commented Poole: "We understood that insulating the pumps in a durable structure and equipping it with space heaters and temperature controls was the most cost-effective, dependable solution for our client. With

little human supervision, the automated pumps and piping had to be protected so the enclosure was the ideal solution."

The final step was to enclose the pumps in an 8 x 10-foot house provided by Kysor Panel Systems. The fiberglass enclosure featured ventilation for summer and heat for winter to thoroughly protect the pumps, piping, valves, lighting and control panel housed within the building.

"Our relationship with SRP and their engineering company - URS Corporation - the Washington Division which is located

in Denver, Colorado, led us to several other orders," says Poole. "The most recent orders were for the effluent pond leak detection pumps.

These pumps lay on top of the secondary liner and are used only when, and if, the primary pond liner leaks. If a leak occurs, the level floats and pumps are activated. For this, we used submersible pumps centralized in a pipe with three Teflon wheels for easy installation and servicing."

www.quadna.com
www.srpnet.com